

Replacement Parts

Chemical Metering Pumps



Key Features

- Precision Engineering
- Industrial Grade
- Tubing and Piping Connections
- Guided Check Balls
- Lower Cost
- Wide Chemical Compatibility
- Fits Most Brand

Application

Advantage Controls manufactures a quality line of metering pumps and we recognize that replacement parts don't need to cost as much as the pump.

Most brands of chemical metering pumps use standard size flexible tubing for suction and discharge lines.

We offer a wide range of replacement foot valves, injection valves and other parts that can be used on any other brand as long as the tubing sizes match up. Get the Advantage of pump parts at lower prices with replacement parts from Advantage Controls.

Part Numbers

Individual Assemblies	Part Number
Injection Valve Assembly	INJ- _____
Foot Valve Assembly	FTV- _____
Suction Valve Assembly	SUC- _____
Discharge Valve Assembly	DIS- _____
3-Function Valve Assembly *	3FV- <u>K</u> _____
Priming Valve Assembly	PRI- <u>K F C 1</u>
Accessory Kit Assembly **	ACC- _____
Ball Check Kit (6 ball checks)	BLK- <u>K</u> _____ <u>1</u>

Body Material _____

K Kynar
M Kynar w/ S.S. MNPT valves
S Stainless Steel

Seat Material _____

F Teflon
H Hypalon
V Viton

Ball Material _____

C Ceramic
D Ceramic (Single on discharge)
S Stainless Steel

Connection Material _____

1 3/8" OD Tubing
2 1/4" OD Tubing
K Kynar suct/disch tubing
P 1/4" MNPT
Q 1/4" MNPT disch / 1/4" FNPT suct
R 1/4" FNPT
U 3/8" Black UV resistant
V 3/8" Clear flex suct tubing

* **Note:** 3-function valve assembly part number **3FV-K** incorporate a spring loaded diaphragm and check ball to provide 25 psi back pressure, discharge line check plus positive anti-siphoning of product at the injection point.

** **Note:** Accessory kit assembly part number **ACC** includes the injection valve, foot valve, tubing weight and all tubing for the pump liquid end code selected.

Complete Head Kits

Advantage Controls replacement head kits include the pump head, our unique priming / degassing valve, 4 head bolts, suction and discharge valves with tubing nuts, all seals, diaphragm. Priming not included on SS heads.



Build your Kit

1 = 110 psi and lower
15 = 150 psi and lower
2 = 250 psi and higher

K = Kynar head & fittings
M = Kynar w/ S.S. MNPT valves
S = Stainless head & fittings

F = Teflon seats
H = Hypalon seats
V = Viton seats

C = Ceramic check ball
D = Ceramic (Single on discharge)

1 = 3/8" O.D. tubing
2 = 1/4" O.D. tubing
P = 1/4" MNPT
Q = 1/4" MNPT disch / 1/4" FNPT suct
R = 1/4" FNPT

CKR- _____

Replacement Tubing

- R00097** PE 1/4" O.D.
- R00122** PE 3/8" O.D.
- R00255** Clear Vinyl 3/8" O.D.

Consult factory for complete list of sizes and parts.

Paddlewheel Flow Meter

FLT-BKFC1 Paddlewheel Flow Meter
 (Kynar body & valves)

Get the Advantage



4700 Harold Abitz Dr
 Muskogee, OK 74403
 800-743-7431 phone
 888-686-6212 fax
www.advantagecontrols.com