

# STA 700 DO Series Sensors

## *Dissolved Oxygen*



## Key Features

- Accurate Measurement
- Quick Release Tee
- Option Float Mount
- Solid State Design
- Simple 4-20mA Output
- Easy Connection to MegaTron Controllers

## Application

These compact in-line sensors provide monitoring and dissolved oxygen in industrial water systems with single or dual 4-20mA outputs.

Advantage Controls makes integration simple and convenient with our pre-fab options and no requirement for an external power supply and mA output isolator.

MegaTron line of controllers with a 4-20 mA input can power the sensor and provide accurate relay control with standard set point, high/low alarm, feed limit timer and daily max feed for proportional chemical concentration control. Add optional web communications for maximum customer satisfaction and performance.

## Build a Model Number

STA - \_\_\_\_\_ - \_\_\_\_\_

### Optics

- 773** = DO (0.004-20mG/L or 0-200%) single output, CPVC body, 30' cable 7 pin, no tee
- 773T** = DO (0.004-20mG/L or 0-200%) single output, CPVC body, 30' cable, 7 pin, 1" CPVC tee, 75 psi max
- 772TP** = DO (0.004-20mG/L or 0-200%) & temp (2 outputs\*\*), 30' cable, 8 pin, CPVC body and tee, 120 psi

### Wiring

- 1** = Standard 50" quick release cable with stripped ends
  - 2** = 50" quick release cable with one mA pre-wired to separately order Advantage controller
  - 3** = 50" quick release cable with two mA's pre-wired to separately order Advantage controller
- \*\* use wiring option 3 on dual output sensors if the second mA output is to be wired.

### Pre-Fab

- X** = Probe and tee not installed
- Y** = Probe and tee pre-installed in controller or pre-fab plumbing (must have Advantage controller or pre-fab ordered as separate line item on same order)

### Specifications

Sensitivity:	<1 ppb typical	Warm Up Time:	5 seconds
Input Voltage:	22-26 VDC	Temperature:	0°-50°C
Signal Output:	4-20 mA	Mounting Tee:	¾" FNPT PVC

### Parts & Accessories

- A-53705 Floating mount kit for STA-733
- A-53712 Replacement DO membrane for STA-772TP
- A-53723 Replacement DO membrane for STA-733
- A-50705 50' extension cable for 8 pin cable STA-772P
- CABLE-7P-EXT25 25' extension for 7 pin cable STA-773
- CABLE-7P-EXT50 50' extension for 7 pin cable STA-773
- MA-WB Bluetooth programming box with 7-pin connectors for 500 and 730 sensors
- MA-CR Bluetooth programming box with 8-pin connectors for 525, 588 and 772 sensors

**Get the Advantage**



4700 Harold-Abitz Dr  
Muskogee, OK 74403  
800-743-7431 Phone  
888-686-6212 Fax  
[www.advantagecontrols.com](http://www.advantagecontrols.com)